



9270-02-01

STANDARD FEATURES: OPTIMAX™ BLOWERS

- 2-position adjustable handle
- Durable, solid, front wheel is an available option for all Optimax blowers
- Continuously-welded steel housing
- One-piece engine deck
- Integrated front / side discharge
- Steel impeller with reverse angle
- 5-year warranty*

*Engines are warranted separately by manufacturer.



9160-04-01



9390-02-01



9570-14-01

Push Optimax™ Blowers

Product No.	9160-04-01	9270-02-01	9270-06-01	9390-02-01	9390-06-01	9570-04-01
CE Product No.	N/A	9270-02-59	N/A	9390-02-59	N/A	N/A
Engine	B & S® XR 6.5	Honda® GX270	Kohler® CH395	Honda® GX390	Kohler® CH440	B & S® Vanguard™
Displacement (cc)	208	270	277	389	429	570
Fuel Capacity, gal (l)	0.8 / (3.0)	1.4 (5.3)	1.95 (7.4)	1.6 (6.1)	1.95 (7.4)	1.75 (6.7)
Impeller Diameter, in (cm) / # Blades	17 (43.2) / 7	17 (43.2) / 7	17 (43.2) / 7	17 (43.2) / 7	17 (43.2) / 7	17 (43.2) / 9
Air Flow (CFM)	1,700	2,260	2,260	2,530	2,530	2,850
Air Speed, mph (km/h)	190 (305.8)	143 (230.1)	143 (230.1)	160 (257.5)	160 (257.5)	179 (288.1)
Air Flow Control	Manual	Remote	Remote	Remote	Remote	Remote
Front Tires, in (cm)	10 (25.4) Pneumatic					
Rear Tires, in (cm)	10 (25.4) Pneumatic	12 (30.5) Pneumatic				
Dimensions L x W x H, in (cm)	56 x 28 x 42 (142 x 71 x 107)	58 x 28 x 43 (147 x 71 x 109)	58 x 28 x 43 (147 x 71 x 109)	58 x 28 x 43 (147 x 71 x 109)	58 x 28 x 43 (147 x 71 x 109)	58 x 28 x 43 (147 x 71 x 109)
Weight, lbs (kg)	108 (49)	142 (64)	148 (67)	174 (79)	174 (79)	188 (85)

Self-Propelled (SP) Optimax™ Blowers

Product No.	9270-12-01	9390-12-01	9570-14-01
CE Product No.	9270-12-59	9390-12-59	N/A
Engine	Honda® GX270	Honda® GX390	Briggs & Stratton® Vanguard™
Displacement (cc)	270	389	570
Fuel Capacity, gal (l)	1.4 (5.3)	1.6 (6)	1.75 (6.6)
Max Speed Fwd / Rev, mph (km/h)	4.1 (6.6) / 2.5 (4)	4.1 (6.6) / 2.5 (4)	4.1 (6.6) / 2.5 (4)
Transmission	Variable Speed Belt-powered Chain Drive, Open Center Differential		
Impeller Diameter, in (cm) / # Blades	17 (43.2) / 7	17 (43.2) / 7	17 (43.2) / 9
Air Flow (CFM)	2,260	2,530	2,850
Air Speed, mph (km/h)	143 (230.1)	160 (257.5)	179 (288.1)
Air Flow Control	Remote	Remote	Remote
Front Tires, in (cm)	10 (25.4) Pneumatic		
Rear Tires, in (cm)	13 (33.02) Pneumatic Turf Tread		
Dimensions L x W x H, in (cm)	58 x 28 x 43 (147 x 71 x 109)		
Weight, lbs (kg)	202 (91.6)	228 (103.4)	248 (112.5)

ACCESSORIES

Accessory	Item Number	Compatible with:
Parking Brake	4174094	Optimax™ Push models only except 9160
Solid Front Wheel	4173815	All Optimax™ blowers
Tool Holder	4174355	All Optimax™ blowers
Swivel Wheel Kit	9050-00-01	All Optimax™ blowers except for 9570-04-01 and 9570-14-01

